

INTERLOCKING MAT

Ideal for Entrance, Wet Areas,
Washrooms,
Swimming pool Surrounds,
Showers, Spas, Saunas,
Changing Rooms &
Kitchens.



SPECIAL FEATURES


- Unique Design •
- Slip Resistant •
- Easy Cleaning & Maintenance •
- Easily Interlocked •
- Ideal For Barefoot Traffic •
- Lightweight •
- Antibacterially Treated UV-resistant Soft vinyl •
- 100% Recycleable •

INSTALLATION AND MAINTENANCE


Joining tiles together is very easy.
Turn tiles upside down
and connect tiles with a hammer.



Sweep or Wet-Mop the top surface
of mat regularly.



Remove mat from service area, if
there is no drainage in area. if
necessary, hose down the mat with
a garden hose or spary down with
high pressure washer and place mat
back into service.



Tiles are easy to cut to size and shape.
Take note of holes, posts, radiators
etc.If mats need to be cut, make
necessary cuts first with snap-off knife
or secateurs.



Lightweight mat is easy to handle
and it can be roller up for maintenance.
If needed mop or flush service area.

TECHNICAL SPECIFICATIONS

Material	: Antibacterially treated UV-resistant soft vinyl. 100 % recyclable.
Tile size	: 200 x 200 mm
Packaging	: 25 tiles / pkg (= 1 m ²)
Height	: 9 mm
Weight	: 4,1 kg/m ²
Color	: Black, dark grey, brown, terracota, dark beige, pastel blue, turquoise, dark blue, purple, red
Temperature resistance	: -35°C - +70°C
Slip resistance	: DIN 51097: A + B + C DIN EN 13451/15288-1: 30°
Fire classification	: EN 13501: Cfl - s1
Emissions	: ISO 16000-9: TVOC class A+

